CETRIS[®] LASUR

is a cement bonded particleboard with smooth surface coated with pigmented primer and final translucent coloured paint in shades according to the colour table.





Cement bonded particleboard 10 - 32 mm thick with smooth surface coated with pigmented primer and final translucent coloured paint in shades according to the colour table. The coating with translucent paint does not create uniform and compact appearance. On special order also the boards 34, 36, 38 and 40 mm can be delivered. The basic size of the board is 3350 x 1250 mm. Available additional processing of the board is similar as with the CETRIS BASIC boards. The CETRIS LASUR boards are used mainly as facade cladding.

The back side of the CETRIS LASUR board is coated with protective primer of irregular structure and/or appearance and of unsufficient covering power. This coating has not any specific colour shade. Eventual request for white or transparent colour has to be specified when ordering.

CETRIS[®] LASUR nomenclature



Please note: the colour table is approximate only



CIDEM Hranice, a.s., divize CETRIS Nová 223, 735 01 Hranice I - Město

> Phone: +420 581 676 281 E-mail: cetris@cetris.cz www.cetris.cz



The biggest producer of the cement bonded particleboards in Europe

Technical specification:

Basic size: 3350 x 1250 mm

Board thicknesses: 10-12-14-16-18-20-22-24-26-28-30-32 mm on special order also 34-36-38-40 mm

Density: 1150 - 1450 kg/m³

Additional processing: on customer's request: cutting, drilling, chamfering

Surface: smooth, couated with pigmented primer and final translucent coloured paint

Colour shades: according to the CETRIS LASUR colour table



